

## Rotating insulators

Item Number	Type	Total length [mm]	Rib-Ø [mm]	Connection-Ø [mm]
1020	3-Ribs	246 +-3.2	172	80 +-2.5
1021_22	4-Ribs	263.5 +-4.8	178	80 +-2.5
1024	5-Ribs	327 +-5	175	80 +-2.5
1044	6-Ribs	400	175	80 +-2.5

/\* \*/

## Cylindrical post insulators

Item number	Height [mm]	Outer-Ø [mm]	Inner-Ø [mm]	Comment
1004	370 +-4.7	432 +-9.5	min. 355.6	ID gefast
1007	372.5 +-2.5	432 +-9.5	min. 355.6	
1009	500 +-6.3	400 +-9.5	350	
1010	533 +-5	371	327 +-7	
1005	535 +-5	387 +-9.5	327	
1008	535 +-5	365 -15	327 +-7	
1015	520.7 +-2.4	356	305 +-7	
1016	500 +-6.3	390 +-9.5	min. 335	

/\* \*/

## Conical support insulators

Item number	Height [mm]	Lower outer-Ø [mm]	Upper outer-Ø [mm]	Wall thickness
1037	475 +-4.0	430 +-9.0	240 +-8	26 +-2.0
1017	500 +-10	487 +-7.5	328 +-6	25
1003	500 +-5	460 +-11.5	317 +-6.5	30 +-2.5
1001	508 +-6.4	375 +-7.5	267 +-5.5	27.3 +-2.5
1012	520 +-15	450 +-10	350 +-8	25
1014	610 +-10	425 +-10	345 +-8	28.5 +-2.5
1002	700 +-10	375 +-7.5	267 +-5.5	27.3 +-2.5
1013	700 +-10	460 +-11	260 +-6	30 +-2.5
1006	700 +-10	487 +-7.5	264 +-6	min. 25

/\* \*/